

Lembar data produk

Spesifikasi

APC

Green
Premium™



APC Smart-UPS On-Line, 2200VA, Tower, 230V, 8x IEC C13+2x IEC C19 outlets, SmartSlot, Extended runtime, Rail kit excluded

SRT2200XLI

Overview


Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	1980 W
Rated power in VA	2200 VA
Input Connection Type	BS1363A British IEC 60320 C20 Schuko CEE 7 / EU1-16P
Output connection type	8 IEC 60320 C13 2 IEC Jumpers 2 IEC 60320 C19
Cable length	2.44 m
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	CD with software Country-specific detachable power cord Documentation CD Installation guide Removable support feet USB cable Warranty card

Batteries & Runtime

Number of battery filled slots	1
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Battery voltage	72 V

Battery charger power	122 W rated
Battery power in VAH	367 VAh runtime
Battery life	3...5 year(s)
Replacement battery	APCRBC141 
Battery option	SRT72BP 1 1101 VAh SRT72BP 2 1835 VAh SRT72BP 3 2569 VAh SRT72BP 4 3303 VAh SRT72BP 5 4037 VAh SRT72BP 6 4771 VAh SRT72BP 8 6239 VAh SRT72BP 10 7707 VAh
Extended runtime	1

General

Product web sub-family	High density
Number of power module	1400
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Colour	Black
Height	43.2 cm
Width	8.5 cm
Depth	58.4 cm
Product weight	25 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes
Mounting position	Vertical

Input

Network frequency	40...70 Hz auto-sensing
Input voltage limits	100...275 V adjustable (half load)

Output

Maximum configurable power in W	1980 W
Harmonic distortion	Less than 2 %
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Crest factor	3 : 1
UPS type	Double conversion online
Wave type	Sine wave
Bypass type	Internal bypass (automatic and manual)

Maximum configurable power in VA	2200 VA
----------------------------------	---------

Conformance

Product certifications	CE EAC RCM VDE
Marking	CE Mark
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.00...15240.00 m
Acoustic level	55 dBA
Heat dissipation	703 Btu/h
IP degree of protection	IP20

Communications & Management

Free slots	1
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

Surge Protection and Filtering

Surge energy rate	340 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.6 cm
Package 1 Width	81 cm
Package 1 Length	59.9 cm
Package 1 Weight	30.84 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
-----------------	---

Penggantian yang disarankan