

# Lembar data produk

Spesifikasi



## Surge Protection Device, Domae, 1P, T2, 40 kA

DOML01140

### Main

Range of product	Domae
Product or component type	Surge arrester
Poles description	1P
Earthing system	TT TN-S TN-C
Device application	Residential
Product destination	Surge protection device

### Complementary

Surge arrester class type	Type 2
Surge arrester technology	MOV + GDT
[Ue] rated operational voltage	230 V +/- 10 % AC 50/60 Hz
[In] nominal discharge current	15 kA
[Imax] maximum discharge current	40 kA
[Uc] maximum continuous operating voltage	Common mode: 340 V L/PE Common mode: 260 V N/PE Differential mode: 340 V L/N
Response time	< 25 ns
Maximum [Up] voltage protection level	<1.5 kV type 2
[Ut] temporary overvoltage	337 V L/N 5 s withstand 442 V L/PE 5 s withstand 1200 V N/PE 200 ms withstand 1453 V L/PE 200 ms withstand
[Isccl] short-circuit current rating	6 kA
Disconnecter device type	Circuit breaker Domae MCB 20 A curve C
Local signalling	Operating state: flag (green) Fault indication: flag (red)
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	2
Height	81 mm

Width	18 mm
Depth	63 mm
Product weight	125 kg
Colour	White
Maximum residual current	5 mA L/PE
Connections - terminals	Tunnel type terminals (phase and neutral) 1...25 mm <sup>2</sup> Tunnel type terminals (ground) 1...50 mm <sup>2</sup>
Wire stripping length	11 mm
Tightening torque	2 N.m phase and neutral 3.5 N.m earth

## Environment

Standards	EN 61643-11:2011
Product certifications	SNI
IP degree of protection	IP20 IP40 on enclosure
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...70 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.0 cm
Package 1 Width	2.3 cm
Package 1 Length	8.5 cm
Package 1 Weight	118.0 g
Unit Type of Package 2	CAR
Number of Units in Package 2	12
Package 2 Height	8.0 cm
Package 2 Width	9.2 cm
Package 2 Length	27.5 cm
Package 2 Weight	1.494 kg
Unit Type of Package 3	S03
Number of Units in Package 3	144
Package 3 Height	30.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	18.34 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes

<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
<b>RoHS exemption information</b>	<a href="#">Yes</a>
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>Circularity Profile</b>	<a href="#">End of Life Information</a>
<b>WEEE</b>	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

**Penggantian yang disarankan**