


Lembar data produk

Spesifikasi



Easy UPS 3L 300kVA 400V 3:3 UPS, Startup 5x8

E3LUPS300KHS

Overview

| | |
|---------------------|---|
| Presentation | Easy-to-configure, easy-to-use and easy-to-service 300 kVA 3 phase UPS with an exceptional combination of competitive specifications, compact footprint, and highly available parallel and redundant designs. The EcoStruxure connected Schneider Electric Easy UPS 3L is the easy choice for business continuity on your shop floor or in your electrical room. Includes 5x8 start-up service. |
| Lead time | Special Order - Call for Quoted Lead Times |

Main

| | |
|-----------------------------|--|
| Main Input Voltage | 400 V 3 phases |
| Other Input Voltage | 380 V 415 V |
| Main Output Voltage | 400 V 3 phases |
| Other Output Voltage | 380 V 415 V |
| Rated power in W | 300 kW |
| Rated power in VA | 300 kVA |
| Provided equipment | Dust filter Installation manual Start-up service |

Batteries & Runtime

| | |
|--------------------------------------|-------------------------|
| Battery type | External battery system |
| Battery voltage | +/- 216... +/- 300 V |
| Maximum short-circuit current | 35 kA |
| Discharge battery voltage | +/- 172.8... +/- 240 V |

Physical

| | |
|-----------------------|------------------|
| Colour | White (RAL 9003) |
| Height | 197 cm |
| Width | 60 cm |
| Depth | 85 cm |
| Product weight | 449 kg |
| USB compatible | Yes |

Input

| | |
|----------------------------------|---|
| Maximum input current | 540 A |
| Max short time withstand current | 35 kA |
| Input harmonic distortion | Less than 3 % for full load |
| Load power factor | 0.5 leading to 0.5 lagging without derating |
| Input voltage limits | 323...477 V |
| Network frequency | 40...70 Hz |

Output

| | |
|----------------------------------|--|
| Maximum configurable power in VA | 300 kVA |
| Maximum configurable power in W | 300 kW |
| Output frequency | 50 Hz sync to mains 60 Hz sync to mains |
| Output harmonic distortion | < 2% linear load and < 4% non-linear load |
| Output overload operation | 10 minutes at 125% and 60 seconds at 150% |
| UPS type | Double conversion online |

Conformance

| | |
|------------------------|------------------|
| Product certifications | CE EAC RCM |
|------------------------|------------------|

Environmental

| | |
|---------------------------------------|-------------------------|
| Ambient air temperature for operation | 0...30 °C |
| Relative humidity | 0...95 % non-condensing |
| Operating altitude | 0...4921 ft |
| Ambient air temperature for storage | -25...55 °C |
| Storage Relative Humidity | 0...95 % non-condensing |
| Storage altitude | 0.00...14999.82 m |
| Acoustic level | 70 dB |
| Heat dissipation | 59386 Btu/h |
| IP degree of protection | IP20 |

Communications & Management

| | |
|---------------|---------------------------------|
| Control panel | Touch screen LCD user interface |
|---------------|---------------------------------|

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 2117 mm |
| Package 1 Width | 1000 mm |
| Package 1 Length | 800 mm |
| Package 1 Weight | 503 kg |

Offer Sustainability

REACH Regulation [REACH Declaration](#)

EU RoHS Directive [Compliant](#)
[EU RoHS Declaration](#)

Mercury free [Yes](#)

China RoHS Regulation [China RoHS declaration](#)

RoHS exemption information [Yes](#)

Contractual warranty

Warranty 1 year on-site repair or replace with factory authorized Start-Up

Penggantian yang disarankan