

Product datasheet

Specifications

Comb busbar, Easy9 XP, 2P, 63 A, 12 modules



EZ9XP212

Main

Range	Easy9
Product or component type	Comb busbar
Mounting mode	Horizontal
Accessory / separate part category	Connection accessory
Lines description	2L
Length in 18 mm modules	12

Complementary

Number of ways	6 ways 2 L
Poles configuration for 1 way	1 x 2P
Connection pitch	18 mm
Connector type	Tooth
Distance between way	36 mm
Insulation	Insulated
Device presentation	Cuttable
Provided equipment	2 end piece
[Ie] rated operational current	63 A at 40 °C
[Ue] rated operational voltage	230 V AC 50 Hz Ph/N 400 V AC 50 Hz Ph/Ph
[Ui] rated insulation voltage	500 V AC conforming to IEC 61439-1
Mounting location	Top on tunnel type terminals
9 mm pitches	24
Width	220 mm
Colour	Light grey (RAL 7035)
Range compatibility	Easy9 (Easy9 XP)

Environment

Standards	IEC 60439-1 IEC 60664
Fire resistance	850 °C (30 s) conforming to IEC 60695-2-1

Pollution degree	2
------------------	---

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.0 cm
Package 1 Width	2.5 cm
Package 1 Length	21.6 cm
Package 1 Weight	60.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	5.7 cm
Package 2 Width	8.5 cm
Package 2 Length	24.8 cm
Package 2 Weight	665.0 g
Unit Type of Package 3	S03
Number of Units in Package 3	160
Package 3 Height	30.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	11.134 kg

Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)