

# Lembar data produk

Spesifikasi



## shunt trip voltage release MX - 250 V DC

LV429394

### Main

|                              |  |
|------------------------------|--|
| Range                        | ComPacT  |
| Range of product             | ComPact NSX100...250<br>ComPacT NSX100...250 new generation<br>ComPact NSX400...630<br>ComPacT NSX400...630 new generation<br>ComPact NSX100...250 DC<br>ComPacT NSX100...250 DC new generation<br>ComPact NSX100...250 DC PV<br>ComPacT NSX100...250 DC PV new generation<br>ComPact NSX400...630 DC<br>ComPacT NSX400...630 DC new generation<br>ComPact NSX400...630 DC PV<br>ComPacT NSX400...630 DC PV new generation |
| Device short name            | MX   |
| Product or component type    | Voltage release  |
| Device application           | Control  |
| Voltage release type         | Opening coil<br>Shunt trip release   |
| [Uc] control circuit voltage | 250 V DC   |
| Range compatibility          | ComPacT new generation (ComPacT NSX new generation)<br>ComPacT new generation (ComPacT NSX DC new generation)<br>ComPact (ComPact NSX)<br>ComPact (ComPact NSX DC)<br>EasyPact (EasyPact CVS)<br>PowerPact (PowerPact Multistandard)   |

### Complementary

|                               |  |
|-------------------------------|--|
| Operating threshold           | 0.7...1.1 x Un opening                             |
| Response time                 | 50 ms  |
| Control signal type           | Maintained<br>Impulse                              |
| Impulse duration              | $\geq 20$ ms                                       |
| Supply inrush power           | 10 W   |
| Auxiliary connection terminal | Spring 0.5...1.5 mm <sup>2</sup> (AWG 20...AWG 16) |
| Wire stripping length         | 7 mm   |

### Packing Units

|                              |     |
|------------------------------|-----|
| Unit Type of Package 1       | PCE |
| Number of Units in Package 1 | 1   |

|                              |          |
|------------------------------|----------|
| Package 1 Height             | 4.5 cm   |
| Package 1 Width              | 4.7 cm   |
| Package 1 Length             | 6.2 cm   |
| Package 1 Weight             | 116.0 g  |
| Unit Type of Package 2       | BB1      |
| Number of Units in Package 2 | 10       |
| Package 2 Height             | 7.1 cm   |
| Package 2 Width              | 10.5 cm  |
| Package 2 Length             | 23.6 cm  |
| Package 2 Weight             | 1.219 kg |
| Unit Type of Package 3       | S03      |
| Number of Units in Package 3 | 60       |
| Package 3 Height             | 30.0 cm  |
| Package 3 Width              | 30.0 cm  |
| Package 3 Length             | 40.0 cm  |
| Package 3 Weight             | 7.698 kg |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information       |
| RoHS exemption information | Yes   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| PVC free                   | Yes   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 12 months |
|----------|-----------|

## Penggantian yang disarankan