


Lembar data produk

Spesifikasi



time delay relay - for voltage release MN - 48 V AC - 50/60Hz

LV429426

⚠ **Telah dihentikan pada:** 10 Oktober 2022

⚠ **Dihentikan**

Main

Device short name	MN delay unit
Product or component type	Time delay relay
Device application	Control
Range compatibility	ComPact (ComPact NSX) PowerPact (PowerPact Multistandard) ComPact (ComPact NSX DC) EasyPact (EasyPact CVS) ComPact (ComPact NSXm)
Voltage release type	Undervoltage release
[Uc] control circuit voltage	48 V AC 50/60 Hz

Complementary

Impulse duration	200 ms
Time delay range	200 ms
Threshold tripping voltage	0.35...0.7 x Un opening 0.85 x Un closing
Supply holding power	4.5 VA
Supply inrush power	200 VA
Mounting mode	External mounting
Response time	<= 200 ms

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.0 cm
Package 1 Width	7.8 cm
Package 1 Length	8.6 cm
Package 1 Weight	133.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	15
Package 2 Height	30.0 cm

Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	2.482 kg

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	12 months
----------	-----------

Penggantian yang disarankan