

# Yuasa Technical Data Sheet



## Yuasa REW45-12 Industrial VRLA Battery

### Specifications

Nominal voltage (V)	12
10m rate Constant Power (Typ) to 9.6V at 20°C (W/Block)	252
10m rate Constant Power (Typ) to 1.6V/cell at 20°C (W/Cell)	42
10-hr rate Capacity to 1.8V/Cell at 20°C (Ah)	6.96
20-hr rate Capacity to 1.75V/Cell at 20°C (Ah)	8

### Dimensions

Length (mm)	151 (±0.5)
Width (mm)	64 (±0.5)
Height (mm)	94 (±0.5)
Height over terminals (mm)	97,5 (±0.5)
Mass (kg)	2.7

### Terminal Type

FASTON - Quickfit / release (JST where stated)	6.35
--	------

### Operating Temperature Range

Storage (in fully charged condition)	-15°C to +45°C
Charge	-15°C to +45°C
Discharge	-15°C to +45°C

### Storage

Capacity loss per month at 20°C (% approx.)	3
---	---

### Case Material

Standard	ABS (UL94:HB)
----------	---------------

### Charge Voltage

Float charge voltage at 20°C (V)/Block	13.65 (±1%)
Float charge voltage at 20°C (V)/Cell	2.275 (±1%)
Float Chg voltage tmp correction factor from std 20°C (mV)	-3
Cyclic (or Boost) charge Voltage at 20°C (V)/Block	14.5 (±3%)
Cyclic (or Boost) charge Voltage at 20°C (V)/Cell	2.42 (±3%)
Cyclic Chg voltage tmp correction factor from std 20°C (mV)	-4

### Charge Current

Float charge current limit (A)	No limit
Cyclic (or Boost) charge current limit (A)	2

### Maximum Discharge Current

1 second (A)	105
1 minute (A)	42

### Impedance


Measured at 1 kHz (mΩ)	24
------------------------	----

### Design Life & Approvals

EUROBAT Classification: General Purpose	6 to 9 years
Yuasa design life at 20°C (yrs)	up to 10 years



### Layout



### 3rd Party Certifications

ISO9001 - Quality Management Systems  
UNDERWRITERS LABORATORIES Inc.



### Safety

#### Installation

Can be installed and operated in orientations up to 90° from the upright position.

#### Handles

Batteries must not be suspended by their handles (where fitted).

#### Vent valves

Each cell is fitted with a low pressure release valve to allow gasses to escape and then reseal.

#### Gas release

VRLA batteries release hydrogen gas which can form explosive mixtures in the air. Do not place inside a sealed container.

#### Recycling

YUASA's VRLA batteries must be recycled at the end of life in accordance with local and national laws and regulations.

