

**NPE-1500-U**

**NETYS PE 1500VA UNIVERSAL**



Protection for small office, personal or point-of-sale applications.

**Strong points**

- Ideal and cost-effective protection for SOHO or POS applications
- Easy to use
- A solution for network power cuts and voltage fluctuations
- Simplified connection
- Protection for your data line

**General characteristics**

- Minitower case.
- Step Wave, AVR function (Automatic Voltage Regulation).
- Control panel with LCD display.
- LOCAL VIEW software for local UPS monitoring.
- NTP data line suppressor.
- Up to 6 UPS output sockets.

**Compliance with standards**

- IEC/EN 62040-1, IEC/EN 62040-2
- AS 62040.1.1, AS 62040.1.2, AS 62040.2
- CE
- RCM (E2376)

**Link to the reference**



<https://emea.socomec.com/en/reference/NPE-1500-U>

**Classification**

UNSPSC	39121011
ETIM Class	EC000382
IGCC	4149

**Commerce**

Description	NeTYS PE 1500VA/900W 230V 50/60Hz BATTERY INCLUDED WITH AVR, STEPWAVE 1xUSB
Effective date	2016-07-31
Offer Life Cycle Code	40
Country of origin	CN

**ETIM - Mechanical characteristics**

Height [mm]	182
Width [mm]	130
Depth [mm]	320
Weight [kg]	12

**ETIM - Technical features**

Potential free switch contact	No
-------------------------------	----

**Logistics**

GTIN/EAN	8027122635745
Customs number	8504409590
Price unit	PC
Weight of the packing unit [kg]	12
Length of the packing unit [m]	0.32
Width of the packing unit [m]	0.13
Depth of the packing unit [m]	0.182

**Technical Characteristics**

Height [mm]	182
Width [mm]	130
Depth [mm]	320
Weight [kg]	12
In/out	1/1
Output voltage	230
Rated frequency	50/50
Sn [kVA]	1.5
Pn [kW]	0.9
Conf	M2
Input voltage	230
Rate (min)	1.5
Rate (max)	1.5
Life Time	03-05
Typical Backup Time [min]	3
Configuration	Line-Interactive UPS with AVR